

DECKOVER – SPLIT TILT



CAM
SUPERLINE

DECKOVER – SPLIT TILT



Knife Edge Approach (optional)



Dual Adjustable Cushion Cylinders



Locking Mechanism

STANDARD FEATURES

- Steel Plated Tongue
- Dexter EZ Lube Axles (Oil Bath on 8 Ton)
- Slipper Spring Suspension
- Electric Brakes (2) Axles
- Adjustable Dual Hydraulic Cushion Cylinders
- LED Lights – Rubber Mounted
- Stake Pockets and Rub Rail
- Adjustable 2-5/16" Ball Coupler or Pintle
- 12K Bolt-on Drop Leg Jack
- Hemlock Deck (Oak on 8 Ton)
- Tool Box
- Rear Impact Guard
- Mud Flaps
- D-Ring Tie Downs (8) – 5/8"
- Solar Charged Breakaway
- Sealed Wiring Harness
- 7-Way RV Plug
- Safety Chains
- Epoxy Primer
- Polyurethane Paint Finish
- Colors (standard): Black, Yellow, Red, Gray, Orange & Blue
- Two Year Warranty

SPECIFICATIONS

Model#	6CAM824DOSTT	7CAM824DOSTT	8CAM824DOSTT
GVWR:	13,800 lbs.	16,100 lbs.	18,400 lbs.
Empty Weight:	4,480 lbs.	4,580 lbs.	5,130 lbs.
Payload:	9,320 lbs.	11,520 lbs.	13,270 lbs.
Deck Length:	24' (4' Stat., 20' Tilt)	24' (4' Stat., 20' Tilt)	24' (4' Stat., 20' Tilt)
Overall Width:	96"	96"	96"
Deck Height:	35"	35"	36"
Axle Capacity:	6,000 lbs.	7,000 lbs.	8,000 lbs.
Radial Tire Size:	235/80R16LRE	235/80R16LRE	215/75R17.5LRH
Main Frame & Tongue:	8" I-Beam @ 10#	8" I-Beam @ 10#	8" I-Beam @ 13#
Crossmembers:	3" Channel @ 4.1#	3" Channel @ 4.1#	3" Channel @ 4.1#

OPTIONS AVAILABLE

- Extra Deck Width (102")
- Power Up & Power Down
- Spare Tire & Wheel
- Spare Tire Mount
- Oak Deck
- Winch Mount
- Hydraulic Surge Brakes (Free Backing)
- Torflex Axles
- Forklift Tread Package
- Underbody Tool Box (14"x16"x36")
- Gooseneck with Adjustable Coupler and Dual 12K Jacks
- 3/16" Diamond Plate Decking
- Knife Edge Approach
- Aluminum Wheels
- Wireless Remote (Power Option Only)
- Additional D-Ring Tie Downs – 5/8"
- 25K Coupler
- Undercoating
- Custom Colors



Authorized Dealer

Printed in the USA

CAM
SUPERLINE

www.camsuperline.com

CAM Superline, Inc.

4763 Zane Miller Drive • Waynesboro, PA 17268
(800) 378-7623 • Fax (800) 279-7578