

DECKOVER – FULL TILT



CAM
SUPERLINE

DECKOVER – FULL TILT

STANDARD FEATURES

- Steel Plated Tongue
- Dexter EZ Lube Axles (Oil Bath on 8 Ton)
- Slipper Spring Suspension
- Electric Brakes (2) Axles
- Adjustable Dual Hydraulic Cushion Cylinders
- LED Lights – Rubber Mounted
- Stake Pockets and Rub Rail
- Adjustable 2-5/16" Ball Coupler or Pintle
- 15K Bolt-on Drop Leg Jack
- Hemlock Deck (Oak on 8 Ton)
- Tool Box
- Mud Flaps
- D-Ring Tie Down (6)
- Solar Charged Breakaway
- Sealed Wiring Harness
- 7-Way RV Plug
- Safety Chains
- Epoxy Primer
- Polyurethane Paint Finish
- Colors (standard): Black, Yellow, Red, Gray, Orange & Blue
- Two Year Warranty

SPECIFICATIONS

Model#	5CAM820DOTT	6CAM820DOTT	7CAM820DOTT	8CAM820DOTT
GVWR:	11,960 lbs.	13,800 lbs.	16,100 lbs.	18,400 lbs.
Empty Weight:	3,850 lbs.	3,930 lbs.	4,030 lbs.	4,580 lbs.
Payload:	8,110 lbs.	9,870 lbs.	12,070 lbs.	13,820 lbs.
Deck Length:	20'	20'	20'	20'
(Includes 4' Approach)				
Overall Width:	96"	96"	96"	96"
Deck Height:	34"	35"	35"	36"
Axle Capacity:	6,000 lbs.	6,000 lbs.	7,000 lbs.	8,000 lbs.
Radial Tire Size:	225/75R16LRD	235/80R16LRE	235/85R16LRG	215/75R17.5LRH
Main Frame & Tongue:	8" I-Beam @ 10#	8" I-Beam @ 10#	8" I-Beam @ 10#	8" I-Beam @ 13#
Crossmember:	3" Channel @ 4.1#	3" Channel @ 4.1#	3" Channel @ 4.1#	3" Channel @ 4.1#

OPTIONS AVAILABLE

- Extra Deck Width (102")
- Extra Deck Length (22' and 24')
- Power Up & Power Down
- Spare Tire & Wheel
- Spare Tire Mount
- Oak Deck
- Hydraulic Surge Brakes (Free Backing)
- Torflex Axles
- Forklift Tread Package
- Gooseneck with Adjustable Coupler and Dual Jacks
- 3/16" Diamond Plate Decking
- Aluminum Wheels
- Wireless Remote (Power Option Only)
- Undercoating
- 25K Coupler
- Additional D-Ring Tie Downs
- Custom Colors



Tongue Area



Gooseneck



Authorized Dealer

CAM
SUPERLINE

www.camsuperline.com

CAM Superline, Inc.

4763 Zane Miller Drive • Waynesboro, PA 17268
(800) 378-7623 • Fax (800) 279-7578